

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 May 2003 (08.05.2003)

PCT

(10) International Publication Number
WO 03/038839 A1

(51) International Patent Classification⁷: H01B 7/04, 7/32

(21) International Application Number: PCT/US02/34780

(22) International Filing Date: 30 October 2002 (30.10.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/335,423 31 October 2001 (31.10.2001) US

(71) Applicant: BAKER HUGHES INCORPORATED
[US/US]; 3900 Essex Lane, Suite 1200, Houston, TX
77027 (US).

(72) Inventor: BUSSEAR, Terry, R.; 3422 Ashmere Cove,
Round Rock, TX 78681 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN,
YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR FIBER OPTIC MONITORING OF DOWNHOLE POWER AND COMMUNICATION CONDUITS



(57) Abstract: A method and apparatus for fiber optic monitoring of downhole power and/or communication conduits employs optic fibers near such conduits or even within an encapsulation of said conduits to monitor integrity thereof.

WO 03/038839 A1

BEST AVAILABLE COPY

METHOD AND APPARATUS FOR FIBER OPTIC MONITORING OF DOWNHOLE POWER AND COMMUNICATION CONDUITS

5

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of an earlier filing date from U.S. Serial Number 60/335,423 filed October 31, 2001, the entire contents of which is incorporated herein by reference.

10

BACKGROUND

Modern well construction operation and maintenance requires that power and communication pathways be extended over long distances in the downhole environment. Necessarily then, the conduits employed to provide such pathways are subjected to significant deleterious effects of the downhole environment. Conduits suffer impacts and abrasion, during run-in, and can be damaged or rendered inoperable thereby. Because of the distances involved, inter alia, a power or communication conduit which has become inoperative might not be immediately apparent at the surface of the well. This can result in costly delays of production if power or signals are not reaching the intended targets.

20

SUMMARY

A method for monitoring the power and/or signal conduits whether in copper, optic fiber, or any other type of conductor, in a well and an apparatus therefore employs optic fiber(s) to gain information regarding condition of the conduits. Changes in light conductivity and/or reflectivity along a fiber are indicative of strain or stress in the optic fiber. By measuring such changes, one can extrapolate the condition of the power or communication pathway.

25

An apparatus is disclosed including structure by which the method can be performed.

30

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings wherein like elements are numbered alike in the several FIGURES:

Figure 1 is a perspective cross-section view of a power or communication conduit having optic fibers embedded in an encapsulation matrix thereof;

Figure 2 is a schematic cross-sectional view of a portion of a wellbore having a restriction therein and illustrating a cross-coupling clamp-type protector; and

Figure 3 is an alternate arrangement wherein an optic fiber is proximate connections to determine the state the connections are in.

10

DETAILED DESCRIPTION

Each of the iterations of the monitoring concept disclosed herein is related in that they rely upon the changing optical properties of optical fibers when the fibers are subjected to strain, stress, heat, breakage, etc. By measuring the degradation or change of light transmissivity, backreflection and/or measuring the reflectivity and by employing elapsed time as an additional factor in the measurement, a very accurate construction of the conditions affecting that fiber can be made. The conditions actually affecting the power or communications conductors(s) with which the fiber is associated are likely to be very similar. In order to further enhance accuracy of the construction of conditions, additional fibers may be employed each being individually queried and then an average may be taken among the fibers such that representation of strain, stress, heat, breakage, etc. can be derived.

Reflectivity and transmissivity are related to H^+ loading and excessive thermal exposure.

Backreflection is related to integrity of connections within the fiber channel. Referring to Figure 1, a power/and or communications conduit is illustrated. In the vernacular, such a conduit illustrated is often referred to as an "umbilical". It will be appreciated that an umbilical is but one embodiment of the method and apparatus described herein and that the disclosure hereof applies to any conduit for power or communications in the downhole environment. The conduit 10 comprises an encapsulant material 12 which exhibits structural integrity and abrasion resistance to the extent necessary to ensure its usefulness in the downhole environment. Material

12 may be a plastic material and may be polymeric. In order to enhance the manufacturability of conduit 10 the material may be extrudable or moldable (although other means of manufacture are also contemplated). Abrasion resistance and crush resistance are provided to conductors encapsulated therein.

5 In the embodiment illustrated in Figure 1, three sensing fibers 14 are employed. The illustration further includes crush resistant cable members 16 which each comprise a plurality of individual lines twisted into each cable member 16. These comprise stiffening material such as metal, steel in solid form or twisted form, braided steel wool, braided mineral wool, fiberglass, polyaramid fibers, carbon fibers,
10 etc. and combinations including at least one of the foregoing as well as other materials suitable to add strength to the umbilical. In this embodiment one of the cable members 16 also includes a centrally disposed and protected insulated electrical conductor 18 while the other cable member 16 includes a fiber optic conductor 20 protected therein. It will be understood that Figure 1 is illustrative only and that fewer
15 or other conductors or sensing fibers may be substituted, providing an elongated sensing member is in contact with the encapsulant which itself is in contact with a conductor.

Each of the one or more elongated sensing members which may be optic fibers are measured for light conductivity, transmissivity, etc. as stated hereinbefore as a
20 measure of what strain or stress the conduit 10 is under at any given time or is experiencing over time. As noted above, change in measured light properties provide a calculatable indication of condition of the conduit 10 downhole.

In another embodiment, a single optic fiber is employed as the conductor and is measured to monitor its own condition using the same parameters discussed above.

25 By monitoring periodically or continuously, as desired, an accurate picture of the condition of the conduit can be generated. In addition, and particularly importantly, upon installation of a tool, the operator of the well will know if a conduit has been compromised beyond usability. This is early notification that the device should be pulled. Where in the prior art it would not be known until the tool was
30 installed, tested and in service, the device and method disclosed herein provides notification as early as an occurrence is measurable and so avoids wasted time or loss of the usability of the system in the near future. Time Domain Reflectometry could

then be used to determine the location the fault and save time during the repair operations.

Related to Figure 1 is Figure 2 wherein the optic fiber sensing arrangement and method described is particularly useful. Figure 2 illustrates schematically a cross-coupling clamp-type protector 62 which is a commercially available device intended to protect a conduit 10 at the location of a tubing coupling 54. As is known to one of skill in the art, were the protector 62 to be omitted, significant impact would be visited on conduit 10 because of the large OD at the coupling 54. A restriction 60 in the wellbore can be caused by any number of things, the exact cause not being germane to the functioning of the method and apparatus herein described. What is important to note is that while in a system having multiple cross-coupling clamps, a conduit 10 is spaced from borehole wall 64, when the coupling protectors 62 straddle a restriction 60 (only one of the couplings shown), the restriction may contact conduit 10. Conduit 10 is at that point subject to significant abrasion and compressive loading. As one of skill in the art appreciates this occurs primarily during run-in. The method and apparatus hereof provides information to the operator regarding condition of conduit 10 including any conditions that will require its removal from the well and replacement. By having knowledge of a significantly damaged condition during the run-in process, the additional time and effort of finishing the process, to only then discover the problem, is avoided.

The apparatus and method described is also useful in a related way to determine when the proper radial clamping force is created in a cross-coupling clamp-type protector by monitoring strain in the fiber(s) 14. Additionally, whether or not proper clamping force has been maintained can be monitored during deployment and throughout the life of the tool or the well. Any change in clamping force is apparent including loss of the clamp altogether. The method and apparatus work in this connection identically to the way in which they have been described above. What is done with the data is slightly different. In this embodiment a specific amount of strain is a target. Thus, the finding of strain in the optic fiber is not a warning sign, but rather is an indicator relative to which the installation strain caused by the clamp may be adjusted until the indicator indicates a selected strain on the fiber. The proper

strain having been reached, the protector is properly installed. After installation, a change in the selected strain indicates a loosening or loss of the clamp.

In another embodiment, and referring to Figure 3, an optic fiber alone or with an optic sensor 32 is employed to monitor the condition of electrical connectors at a splice location. As stated hereinabove, temperature affects light travel through optic fibers. By monitoring the change, heat to which the fiber is subjected can be evaluated. With age, electrical connectors can develop corrosion. As corrosion affects the interface between two or more conductors, heat is generated. The more heat generated, generally the more corrosion is present. The heat is due to resistance caused by the corrosion. The amount of heat sensed either at a particular splice or averaged over a number of splices is easily correlated to the degree of corrosion which can then be used to extrapolate expected balance or life span of the connection of plurality of connections. Other optical sensors may also be employed to monitor other conditions that may occur at the connector, alone or in addition to monitoring the temperature change. Strain, stress, fluid ingress, etc may be monitored.

In the illustrated embodiment of Figure 3, conductors 34 and 36 appearing at the left hand side of the illustration have any type of conventional terminus 38, 40 which connects to connectors 42, 44 at interface 46, 48. These connectors operably connect conductors 34, 36 to 50, 52 (right hand side). Since connections are commonplace in the wellbore the ability to monitor temperature thereat provides valuable time to take desired action which may be to simply produce the well until failure or possibly to provide time necessary to order repair parts or schedule maintenance. Repair parts often will not be on hand and availability of equipment and personnel to perform repairs may not be readily available. With the device and method disclosed herein there is time to obtain replacement parts or make determinations regarding well life versus cost of repair, etc.

While preferred embodiments have been shown and described, various modifications and substitutions may be made thereto without departing from the spirit and scope of the invention. Accordingly, it is to be understood that the present invention has been described by way of illustration and not limitation.

CLAIMS

- CLAIM 1.** A communications or power conduit for a wellbore comprising:
an encapsulation material;
at least one communication or power conductor embedded in the
5 encapsulation material; and
at least one optic fiber embedded in the encapsulation material.
- CLAIM 2.** A communications or power conduit for a wellbore as claimed in claim
1 wherein said encapsulation material is a polymeric material.
- 10 **CLAIM 3.** A communications or power conduit for a wellbore as claimed in claim
1 wherein said encapsulation material is abrasion resistant.
- CLAIM 4.** A communications or power conduit for a wellbore as claimed in claim
15 1 wherein said conduit further includes at least one reinforcing member.
- CLAIM 5.** A communications or power conduit for a wellbore as claimed in claim
4 wherein said at least one reinforcing member further includes a conductor.
- 20 **CLAIM 6.** A communications or power conduit for a wellbore as claimed in claim
4 wherein said at least one reinforcing member is a cable formed of twisted stiff
material.
- CLAIM 7.** A communications or power conduit for a wellbore as claimed in claim
25 6 wherein said stiff material is metal.
- CLAIM 8.** A communications or power conduit for a wellbore as claimed in claim
6 wherein said stiff material is polyaramid fiber.
- 30 **CLAIM 9.** A communications or power conduit for a wellbore as claimed in claim
6 wherein said stiff material is fiberglass.

CLAIM 10. A communications or power conduit for a wellbore as claimed in claim 6 wherein said stiff material is carbon fiber.

5 CLAIM 11. A communications or power conduit interface for a wellbore comprising:
at least one conductor and conductor connector; and
at least one optic fiber located proximate said conductor connector to monitor condition of the conductor connector.

10 CLAIM 12. A communications or power conduit interface for a wellbore as claimed in claim 11 wherein said fiber further includes an optical temperature sensor.

CLAIM 13. A communications or power conduit interface for a wellbore as claimed in claim 11 wherein said fiber further includes a strain sensor.

15 CLAIM 14. A communications or power conduit interface for a wellbore as claimed in claim 11 wherein said fiber further includes a chemical sensor.

CLAIM 15. A communications or power conduit for a wellbore as claimed in claim 20 12 wherein said sensor is disposed proximate said conductor to monitor temperature thereof.

CLAIM 16. A communications or power conduit for a wellbore as claimed in claim 25 13 wherein said sensor is disposed proximate said conductor to monitor stress thereof.

CLAIM 17. A communications or power conduit for a wellbore as claimed in claim 14 wherein said sensor is disposed proximate said conductor to monitor fluid thereof.

CLAIM 18. A method for monitoring the condition of a power or communication conductor downhole comprising:

- querying an optic fiber near said conductor;
- measuring a light property of said optical fiber; and
- 5 correlating said light property with a condition of said conductor.

CLAIM 19. A method for monitoring the condition of a power or communication conductor downhole as claimed in claim 18 wherein said property is transmissivity.

- 10 CLAIM 20. A method for monitoring the condition of a power or communication conductor downhole as claimed in claim 18 wherein said property is reflectivity.

CLAIM 21. A method for monitoring the condition of a power or communication conductor downhole as claimed in claim 18 wherein said property is backreflection.

15

CLAIM 22. A method for monitoring the condition of a power or communication conductor downhole as claimed in claim 18 wherein said correlating is mathematical calculation of a physical condition based upon measured light properties of said fiber.

- 20 CLAIM 23. A method for monitoring the condition of a power or communication conductor downhole as claimed in claim 18 wherein said correlating is mathematical calculation of a physical condition based upon measured light properties of said fiber over a period of time.

- 25 Claim 24. A method for monitoring the condition of a power or communication conductor downhole as claimed in claim 18 wherein said correlating is mathematical calculation of the location of the point of interest based upon measured light properties of said fiber.




FIG. 1





FIG. 2

*FIG. 3*

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 02/34780

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 H01B7/04 H01B7/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 522 464 A (THOMPSON ROBERT E ET AL) 11 June 1985 (1985-06-11)	1
A	column 4, line 23 -column 14, line 18; figure 1	2-10
X	WO 00 75933 A (SCHLUMBERGER HOLDINGS; SCHLUMBERGER CA LTD ; SCHLUMBERGER SERVICES) 14 December 2000 (2000-12-14)	1
A	page 10, line 4 -page 11, line 11; figure 2	2-10
A	FR 2 750 243 A (TELECOMMUNICATIONS SA) 26 December 1997 (1997-12-26)	1-10
	page 3, line 4 -page 5, line 20; figure 1	
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

G document member of the same patent family

Date of the actual completion of the international search

7 February 2003

Date of mailing of the international search report

17/02/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+31-70) 340-3016

Authorized officer

Demolder, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 02/34780

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 840 331 A (ALSTHOM CGE ALCATEL) 6 May 1998 (1998-05-06) column 2, line 10 -column 4, line 33; figure 2	1-10
A	EP 0 203 249 A (FELTEN & GUILLEAUME ENERGIE) 3 December 1986 (1986-12-03)	

Form PCT/SA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 02/34780

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4522464	A	11-06-1985	AU 563499 B2	09-07-1987
			AU 1942883 A	07-03-1984
			AU 582498 B2	23-03-1989
			AU 7271387 A	03-09-1987
			AU 586099 B2	29-06-1989
			AU 7271487 A	03-09-1987
			CA 1221861 A1	19-05-1987
			DE 3374443 D1	17-12-1987
			DE 116619 T1	14-03-1985
			EP 0116619 A1	29-08-1984
			ES 8406741 A1	01-11-1984
			FR 2532062 A1	24-02-1984
			GB 2135791 A ,B	05-09-1984
			IT 1163902 B	08-04-1987
			JP 59501560 T	30-08-1984
			MX 7253 E	22-02-1988
			NO 841478 A ,B,	12-04-1984
			SG 90290 G	21-12-1990
			WO 8400820 A1	01-03-1984
WO 0075933	A	14-12-2000	US 2002060070 A1	23-05-2002
			AU 4942300 A	28-12-2000
			GB 2366069 A	27-02-2002
			WO 0075933 A1	14-12-2000
FR 2750243	A	26-12-1997	FR 2750243 A1	26-12-1997
EP 0840331	A	06-05-1998	DE 29618796 U1	05-12-1996
			EP 0840331 A1	06-05-1998
EP 0203249	A	03-12-1986	DE 3518909 A1	27-11-1986
			AT 74688 T	15-04-1992
			DE 3684723 D1	14-05-1992
			EP 0203249 A2	03-12-1986

Form PCT/ISA/210 (patent family annex) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 02/34401

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5356646	A	18-10-1994	NONE	
US 3632962	A	04-01-1972	NONE	
WO 0044269	A	03-08-2000	FR 2788956 A1	04-08-2000
			EP 1146808 A1	24-10-2001
			WO 0044269 A1	03-08-2000
			US 6393973 B1	28-05-2002

Form PCT/ISA/210 (patent family annex) (July 1992)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)